	TECHNICAL DATA SHEET	code	4402FE
		version	3
		date	2007-02-16
	4402FE NON-PAIRED	page	1/2

APPLICATION

Intercom/PA Systems, Sound/Audio Systems.

CONSTRUCTION



1. Conductor

Diameter of conductor	0.96mm (AWG20)
Material	stranded bare copper (7xAWG28)

2. Insulation

Material	PE
Diameter over insulation	1.45 ± 0.05 mm
Wallthickness	0.25 mm

3. Overall Cabling

Colour code	black-red-white-green
-------------	-----------------------

4. Outer shield

Shield	Beldfoil®)
Shield Material	Aluminium / Polyester tape
Shield Thickness Alu	9 µm
Shield coverage	100%
Drainwire	AWG22 (7xAWG30) tinned Cu


4. Sheath

Material	FRNC
Colour	Grey
Nominal thickness	0.38 mm
Nominal diameter	4.30 mm

REQUIREMENTS AND TEST METHODS

Electrical:

Nominal resistance conductor	34 Ω/km
Nominal resistance shield	37 Ω/km
Nom. capacitance conductor to conductor @ 1kHz	110 pF/m
Nom. capacitance cond. to shield + other cond. @ 1kHz	200 pF/m
Testvoltage conductor-conductor	2500 VDC, 3 seconds
Testvoltage conductor-screen	2500 VDC, 3 seconds
Voltage rating	300 V RMS
Maximum continues current per conductor @ 25 °C	3.0 A per conductor @ 25 °C

	TECHNICAL DATA SHEET	code	4402FE
		version	3
		date	2007-02-16
	4402FE NON-PAIRED	page	2/2

Mechanical and physical:

Flame resistance	u.c.
Temperature range processing and operating	-20 to +70 °C
Temperature range storage	-30 to +70 °C
Minimum bending/setting radius	5*D/10*D
Maximum pulling tension	27 N



Belden CDT believes this product to be in compliance with the environmental regulations EU RoHS (Directive 2002/95/EC, 27 January 2003); this is valid for all material produced after the RoHS compliant date for this product.

© Belden Wire & Cable B.V.

All rights are reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner