

### Application

- Horizontal and building backbone cable.
- Support current and future **Category 6 and Category 5 enhanced** applications, such as: 10 Base-T, 100 Base-T, 1000 Base-T (Gigabit Ethernet), FDDI, ATM

### Key features and Standards

- General standards: **ISO/IEC 11801 2<sup>nd</sup> edition (2002)**, **EN 50173 2<sup>nd</sup> edition (2001)**, **ANSI/TIA/EIA 568-B.2 (2002)**

### Construction & Dimensions

- Construction: shielded 4 twisted pairs
- Conductor: solid bare copper
- Conductor diameter: AWG 23 (0,55 mm)
- Conductor insulation material: Polyolefin
- Diameter over insulation: 1,15 mm
- Cross web: Polyolefin
- Shield: Aluminum/polyester foil  
Tinned Copper Braid (>40%)
- Drainwire: AWG 26 solid tinned copper
- Jacket material: FRNC compound
- Outer diameter: 7,50 mm

Pair 1	White-Blue/Blue
Pair 2	White-Orange/Orange
Pair 3	White-Green/Green
Pair 4	White-Brown/Brown

Colour identification according to IEC 60304

### Electrical characteristics (at 20 °C)

Nominal mutual capacitance at 1 kHz	50 nF/km
Maximum conductor DCR	91 Ohm/km
NVP - Nominal Velocity of Propagation	0.70 c
SKEW – Propagation delay difference (100 MHz)	typical ≤ 15 ns/100m
Mean Characteristic Impedance 4-100 MHz <sup>1)</sup>	100 ± 5 Ohm

<sup>1)</sup>: According to cable requirements of ISO/IEC 11801 category 6, Sept. 2002.

### General and environmental characteristics

Temperature range - operation	-20°C - +60°C
Temperature range - installation	+0°C - +50°C
Minimum bending radius - operation	29 mm
Minimum bending radius - installation	58 mm
Maximum pulling tension	50 N
Flame retardancy	IEC 332-1
Caloric value	820 kJ/m
Weight (approx.)	51.0 kg/km
Maximum operating voltage	48 V rms
Maximum continuous current per conductor (25°C)	1.4 A

### Electrical characteristics (at 20 °C)

#### Attenuation

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Max.) <sup>1)</sup>	-	4.0	6.0	7.6	8.5	10.8	15.5	19.9	25.3	29.2	33	dB/ 100m
Typical	[1.9]	3.5	5.5	6.9	7.6	9.7	13.8	17.7	22.4	25.1	28.2	dB/ 100m

#### NEXT (Near end crosstalk)

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Min.) <sup>1)</sup>	-	66	60	57	56	53	48	45	42	41	39	dB/ 100m
Typical	[80]	76	70	67	66	63	58	55	51	49	45	dB/ 100m

#### Power sum NEXT

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Min.) <sup>1)</sup>	-	63	57	54	53	50	45	42	39	38	36	dB/ 100m
Typical	[74]	71	64	62	61	54	53	50	47	46	43	dB/ 100m

#### Power sum ELFEXT

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Min.) <sup>1)</sup>	-	53	45	41	39	35	29	25	21	19	17	dB/ 100m
Typical	[70]	64	57	51	49	45	39	35	31	29	27	dB/ 100m

#### ACR

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Min.) <sup>1)</sup>	-	62.0	54.0	49.4	47.5	42.2	32.5	25.1	16.7	11.8	6.0	dB/ 100m
Typical	[78]	73	65	60	58	53	44	37	29	24	17	dB/ 100m

#### Power sum ACR

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Min.) <sup>1)</sup>	-	59.0	51.0	46.4	44.5	39.2	29.5	22.1	13.7	8.8	3.0	dB/ 100m
Typical	[76]	71	63	58	56	51	42	35	27	22	15	dB/ 100m

#### Return Loss

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	250	MHz
Spec. (Min.) <sup>1)</sup>	-	23.0	25.0	25.0	25.0	23.6	21.5	20.1	18.8	18.0	17.3	dB/ 100m
Typical	[30]	35	40	44	44	44	34	30	25	24	24	dB/ 100m

<sup>1)</sup>: Specification values according to cable requirements of ISO/IEC 11801 category 6, Sept. 2002.

Note: Values between brackets are for information only

### Ordering information

#### MARKING

Text on the cable jacket      Inkjet printing

**BELDEN 7860ENS STP CAT6 4PR AWG23 LSNH ISO/IEC 11801 EN50173 VERIFIED 100 OHM**

Meter marking:                      Yes

#### JACKET COLOUR

GREY	RAL 7032
BLUE	RAL 5015

#### PACKAGING (PUT UP)

500m and 1000m Crate reels