


Product Datasheet
BE46306
Analog Multi-Pair Snake Cable - PVC
24-Pair – 26AWG (0.14mm²)

Rev. 2/ 2005-05-20 2/2

Application

Belden 46-analog-series is a flexible audio snake cable with an overall braid shield. This makes the cable suitable for mobile applications. Jacketed pairs are individually numbered for easy identification.

Construction & Dimensions



1. **Conductor**
2. **Pair**
3. **Outer Shield**
4. **Jacket**

1. **Inner Conductor** Innenleiter - Conduttore Interno – Conducteur – Conductor - Проводник

Material	Stranded (18 x 0.10mm), tinned copper
Diameter	0.14 mm ²

Insulation Isolation – Isolant - Isolamento – aislamiento - Изоляция	
Material	PE
Diameter over insulation	0.48 mm
Color of insulation	White and red, twisted

2. **Pair** Paar – Paire - Pare – Coppia - par - пары

Number of pairs	24
Diameter conductor	1.05 mm
Diameter pair	3.10 mm ± 0.06 mm

2.1 Separating foil	Polyester
2.2 Inner shield	Spiral Serve, tinned copper braid
Coverage	> 90%
2.3 Inner jacket	PVC, Grey
Marking	each pair is numbered (app. 50 times/m)

3. **Outer shield** Gesamtschirm – Tresse générale - Schermatura esterna - blindaje exterior - внешний экран

Outer shield	Tinned copper braid
Coverage	> 90%

4. **Jacket** Aussenmantel – Guaina – Gaine – Revestimiento - Оболочка

Material	PVC
Diameter:	22.4 ± 0.2 mm
Color and text:	see table Marking

Product Datasheet
BE46306
Analog Multi-Pair Snake Cable - PVC
24-Pair – 26AWG (0.14mm²)

Rev. 2/ 2005-05-20 2/2

Requirements and test methods

Electrical characteristics

Mean characteristic impedance 1-6 MHz: 95 Ω ± 20 Ω

Wellenwiderstand - Impedenza Caratteristica Principale - Impédance nominale - Características eléctricas - Электрические характеристики

Nominal capacitance conductor to conductor: 60 pF/m

Kapazitaet (Ader/Ader) - Capacità Nominale Conduttore/Schermo - Capacité nominale entre conducteur et blindage - Capacitancia nominal de conductor a blindaje - Номинальная емкость "проводник-проводник"

Nominal capacitance conductor to shield: 110 pF/m

Kapazitaet (Ader/Schirm) - Capacità Nominale Conduttore/Schermo - Capacité nominale entre conducteur et blindage - Capacitancia nominal de conductor a blindaje - Номинальная емкость "проводник-экран"

Nominal velocity of propagation: 66%

Ausbreitungsgeschwindigkeit - Velocità Nominale di Propagazione - Vitesse de propagation nominale - Velocidad nominal de propagación - Номинальная скорость распространения сигнала

Max. inner conductor DC resistance @ 20 °C: < 260 Ω/km

Gleichstromwiderstand Innenleiter - Resistenza Nominale DC del Conduttore Interno - Résistance du conducteur intérieur - Resistencia CC nominal del conductor interno - Номин. сопротивление пост. току внутреннего проводника

Mechanical and physical characteristics

Temperature range - storage/operation -15°C to +75°C

Temperature range - installation -5 °C to + 75°C

Minimum bending radius 10x Ø cable

Biegeradius - Raggio Minimo di Curvatura - Rayon de courbure minimum - Radio de curvatura mínimo - Минимальный радиус изгиба

Nominal cable weight 624 kg/km

Gewicht - Peso Nominale del Cavo – Poids - Peso nominal del cable - Номинальный вес кабеля



Ordering information

MARKING

Jacket colour	Text
Black	BELDEN BE46306 MULTI-PAIR AUDIO 24 PAIR SHIELDED

Meter marking: yes, MM-YY: month and year of manufacturing

PACKAGING (PUT-UP, +/-10%)

250m

Each reel is labelled with the following data:

Belden Logo, Belden code number, item description, length on the reel and date of manufacturing.